

## Film transport.

The invention is a device for transporting film, in particular photographic film for motion pictures, in particular unperforated film. Unperforated film cannot be transported for motion picture use by conventional transport devices, since there are no perforations for eg. a pulldown claw which is normally used to transport the film intermittently. It is not possible to transport film accurately intermittently at high speeds using friction alone on the film surface. It is desirable to transport unperforated film because the perforations on the film limit the width of the exposed pictures (frames). Perforating film is expensive because of the close tolerances required between perforations, and microscopic dust caused by the perforating process must be removed during manufacture of the film. Unperforated film therefore allows a larger picture, which means improved picture quality at reduced cost.

Transporting perforated polyester-base film using conventional mechanisms, eg. with a pulldown claw, is dangerous for the mechanism if the film jams, because polyester film is very difficult to tear.

It is the purpose of the invention to transport unperforated film without slippage. Perforated film may be transported in one embodiment of the invention, and polyester film may be safely transported. The film is partly penetrated, fully penetrated or indented in various embodiments of the invention, so that it may be accurately transported. Friction against the film to move the film may, in one embodiment, additionally be used. At least one element such as a needle point enters the film for a short distance such as a few hundredths of a millimeter, in one embodiment. It is desirable to use at least two needlepoints or more outside the picture area or possibly four for high speeds for slow motion filming. The needles may be made of steel, sapphire or diamond, for example. The needles may be mounted on a pivoting unit so that the needles may pivot away from the film in case of a film jam. The pivoting unit may be held by friction or a spring-loaded device or by magnetic force, until undue resistance such as jammed film is met, or the unit may mechanically disengage. An electrical contact may be broken to turn off an electric motor driving the transport device, as this occurs. This is especially important when polyester-based film is used, because this type of film is difficult to tear. The film should preferably be transported intermittently with each frame being separately exposed by a shutter such as a rotating shutter, because continuously transported film is usually exposed via a rotating prism which is not desirable. The film may be held steady during exposure of the film to light at the picture aperture by at least one element. The element may be a spring-loaded pressure element such as a pressure plate acting on the back of the film, for example, behind the picture aperture, for example. At least one moveable element may be used in another embodiment, separately, or in conjunction with a pressure element. This moveable element may be rubber-tipped, to apply pressure to eg. the back of the film, at the correct time, so that the film is held steady during exposure. The moveable element may move horizontally or pivot around a bearing or apply pressure against eg. a plate acting against the film via an element such as an eccentric on a rotating shaft. At least one mark, eg. a circular mark may be exposed on the film eg. outside the picture area, eg. between pictures by eg. a light-emitting diode (LED), with a fixed distance from the exposed frame, to provide picture registration reference, eg. for telecine. Two marks may be exposed, if this system is used, eg. as far apart as possible between pictures, next to each other, eg. on the frameline for control of vertical and horizontal picture registration eg. for telecine. The transport device may be eg. eccentric-operated or eg. rotary with eg. radially mounted needles which may, in one embodiment, be moved in a stepping motion. The needles may enter the film at a transport start position, move the film a certain distance to an end position, eg. for a distance of 19mm travel in one embodiment, if 35mm film is used. The film may be transported vertically or horizontally in different embodiments, eg. in a camera.

When transporting unperforated film out of the magazine which stores the film, toothed sprockets which normally engage the perforations in the film can no longer be used. The film loop lengths from the magazine to the film gate and from the film gate (picture aperture) back to the magazine must be controlled. At least one roller with eg. clamps or rollers holding the film against parts of the roller's circumference may be used to correctly transport the film to and from the magazine. This roller may be a friction roller made eg. of polyurethane or silicone rubber or it may pierce (penetrate) or partially pierce the film or indent the film to have a proper hold on the film. Several needles may be radially mounted in tight-fitting holes in the roller, so that eg. very short needle points project radially from the roller, or a friction roller or rollers may be used, or a combination of both. The transport device may pierce the film on one side of the film and the magazine roller or rollers may pierce the film on the other side of the film. The loop length may be monitored eg. mechanically or eg. by infra red light which controls eg. the speed of one or more electric motors on the magazine or connected to the roller or rollers or both. If points are used, they may be offset from needles in the transport device so that piercings in the film from the roller do not correspond to where needles in the transport device enter the film. Provision may be made to absorb or divert any film particles caused by entry of the needlepoints into the film, away, eg. sideways, away from the picture area, away from the film.

A preferred embodiment of the invention is described in the following description and the drawing:

Fig. 1 shows a perspective view of a device for transporting unperforated motion picture film intermittently.

Fig. 1 shows a perspective view of a device for transporting unperforated film 5 intermittently. Two needles 2 are positioned one above the other on the front left of unit 12 and two needles 2 are positioned one above the other on the front right of unit 12. Unit 12 has a swivel point 13 on each side. Unit 12 is supported in a fixed position by spring-loaded ball 15. The pressure of spring-loaded ball 15 in tight-fitting recess 26 on the back of unit 12, which supports unit 12 is overridden when too much vertical resistance by jammed film 5 occurs to needles 2, if film 5 jams. Unit 12 with needles 2 then swivel upwards or downwards depending on whether film 5 is being transported in a forward or reverse direction. When this occurs, electrical contact 14 is broken, turning off battery-driven electric motor 8 which drives device 1. Spring-loaded ball 15 is positioned behind unit 12 on the forward end of element 4. The rear of element 4 is mounted on axle 18 via slot 19 which allows forward and rear travel of element 4. Element 4 has an opening 22. Round eccentric 3 is mounted on axle 25 and is located with very little play between its circumference and the inside of opening 22 within opening 22 of element 4. The rotation of round eccentric 3 determines vertical travel of element 4. Axle 25 is attached to pulley 26 which is connected to electric motor 8 via belt 9. Horizontal movement of element 4 is controlled by the rotating position of eccentric 17, also mounted within opening 22, next to eccentric 3, also on axle 25. As axle 25 is turned by electric motor 8, element 4 with four needles 2 attached to the front of unit 12 is made to move forward so that four needles 2 on the front of unit 12 is made to move forward so that four needles 2 enter a short distance into the rear, non-emulsion side of film 5, to the left and right of the picture area, outside the picture area, near the left and right edges of film 5. Film 5 is supported within channel 23 within wall 16 and wall 21 which abut during transport of film 5. Curvature 24 of channel 23 with film 5 within it, beneath aperture 6, corresponds to the arc made by the tips of needles 2 as needles 2 are transported downwards when transporting film 5, so that the points of needles 2 remain properly engaged in film 5, when transporting film 5. Needles 2 make an arc when transporting film 5 because of the geometry of eccentric 3 driving element 4. Needles 2 move forward and enter the back of film 5 through two slots 27 in rear wall 21, transport film 5 vertically from a start position to an end position. Pressure plate 7 located behind film 5, behind picture aperture 6 holds film 5 steady during exposure of film 5

to light. Pressure plate 7 exerts light constant pressure against the back of film 5 by spring 8. The outside edge area of eccentric 17 acts on vertical side 30 of opening 22 in element 4 and moves element 4 with needles 2 forwards so that needles 2 enter the back of film 5 for a short distance without transfixing film 5. Slot 19 in the back of element 4 around axle 18 allows forward and rearward motion of element 4 with needles 2. Eccenter 3 acts on the bottom horizontal side of opening 22 and moves element 4 with needles 2 downwards, transporting film 5 downwards for a certain distance. Eccenter 3 no longer exerts pressure on the bottom side of opening 22 so that film 5 is no longer transported, but eccentric 17 now exerts pressure on vertical side 29 of opening 22 of element 4 and moves element 4 back so that the points of needles 2 disengage film 5. A rotating shutter (not shown) opens, exposing film 5 to light at aperture 6 and two LEDs 11 each expose a round mark on the emulsion side of film 5, outside the picture area, on the frameline. Eccenter 3 now exerts pressure on top horizontal side of opening 22, moving element 4 with needles 2 upwards to a start position for transporting film 5. Eccenter 3 now no longer exerts pressure on the top horizontal side of opening 22 of element 4 but eccentric 17 acts on vertical side 30 of opening 22 moving element 4 and needles 2 forwards as the shutter closes and the tips of needles 2 enter the back of film 5. Film 5 is now transported downwards again, and continues to be transported intermittently until electric motor 8 is turned off.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000